

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A method of controlling an HVAC system having a heating unit and a cooling unit, the heating unit and the cooling unit each configured to selectively operate in an ~~relatively constant~~ "on" state where each of the heating unit and the cooling unit provide a relatively constant thermal output, or an "off" state, the method comprising:

determining whether the humidity in an inside space is above a predetermined humidity threshold, and if so, operating both the heating unit and the cooling unit in their ~~relatively constant~~ "on" states.

2. (Currently Amended) The method of claim 1 wherein the step of operating both the heating unit and the cooling unit in their ~~relatively constant~~ "on" states is only performed if the temperature in the inside space is below a predetermined cooling set point.

3. (Original) The method of claim 2 wherein only the cooling unit is operated if the temperature in the inside space is above the predetermined cooling set point, regardless of the humidity in the inside space.

4. (Currently Amended) The method of claim 1 wherein the cooling unit includes two or more cooling stages, the method further comprising the steps of:

not operating both the heating unit and the cooling unit in their ~~relatively constant~~ "on" states if two or more cooling stages of the cooling unit are activated.

5. (Currently Amended) A method of controlling an HVAC system having a heating unit and a cooling unit, the heating unit and the cooling unit each configured to selectively operate in an ~~relatively constant~~ "on" state or an "off" state, the method comprising:

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

operating the cooling unit to satisfy a call for cooling for the inside space; and
after the call for cooling has been satisfied, determining if the latent cooling demands have been met, and if not, operating both the heating unit and the cooling unit in their ~~relatively constant~~ "on" states; wherein the thermal output produced by the heating unit is not modulated to match the thermal output of the cooling unit when the heating unit and cooling unit are both in their "on" state.

6. (Original) A method according to claim 5, further comprising the steps of:
deactivating the heating unit and the cooling unit once the latent cooling demands have been satisfied.

7. (Original) A method according to claim 5, further comprising the steps of:
deactivating the heating unit while maintaining the cooling unit if a subsequent call for cooling is provided.

8. (Currently Amended) A method according to claim 5, further comprising the steps of:
deactivating the heating unit and the cooling unit ~~[[of]]~~ if the latent cooling demand has been satisfied and there is no current call for cooling; and
deactivating the heating unit while maintaining the cooling unit if the latent cooling demand has not yet been satisfied but a subsequent call for cooling is provided.

9. (Currently Amended) A method of controlling an HVAC system having a heating unit and a cooling unit, wherein the heating unit and the cooling unit are each configured to selectively operate in an ~~relatively constant~~ "on" state to produce a thermal output, or an "off" state, the HVAC system configured to have a cooling set point temperature, the method comprising:

determining a temperature at a location within an inside space;

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

determining a humidity at a location within the inside space;
selecting a mode in which to operate the HVAC system from among at least the following operating modes depending on the determined temperature and/or humidity:
selecting an "off" mode if the humidity is below a predetermined humidity threshold and the temperature is below a temperature that is related to the cooling set point temperature, the "off" mode having the heating unit and the cooling unit both in their "off" states;
selecting a "cooling" mode if the temperature is above a temperature that is related to the cooling set point temperature, the "cooling" mode having the heating unit in its "off" state and the cooling unit in its ~~relatively constant~~ "on" state; and
selecting a "drying" mode if the humidity is above the predetermined humidity threshold and the temperature is below a temperature that is related to the cooling set point temperature, the "drying" mode having the heating unit and the cooling unit both in their ~~relatively constant~~ "on" states, wherein in the "drying" mode, the combined thermal output of the heating unit and the cooling unit is not zero or substantially zero.

10. (Original) The method of claim 9 wherein the cooling unit includes a first cooling stage and a second cooling stage, the method further comprising the steps of:

predicting or determining whether the first stage of the cooling unit can provide adequate sensible cooling to the inside space; and

selecting the "off" mode if the humidity is below the predetermined humidity threshold and the temperature is below a temperature that is related to the cooling set point temperature;

selecting the "cooling" mode and activating only the first stage of the cooling unit if the humidity is below the predetermined humidity threshold and the temperature is above the temperature that is related to the cooling set point, and the predicting or determining step predicts or determines that the first stage can provide adequate sensible cooling for the inside space;

selecting the "cooling" mode and activating both the first stage and second stage of the cooling unit if the humidity is below the predetermined humidity threshold and the temperature is above the temperature that is related to the cooling set point, and the predicting or determining

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

step predicts or determines that the first stage cannot provide adequate sensible cooling for the inside space;

selecting the "drying" mode and activating only the first stage of the cooling unit if the humidity is above the predetermined humidity threshold and the temperature is above the temperature that is related to the cooling set point.

11. (Original) The method of claim 10 further comprising the step of:

selecting the "cooling" mode and activating both the first stage and the second stage of the cooling unit if the humidity is above the predetermined humidity threshold and the temperature is above the temperature that is related to the cooling set point, and the predicting or determining step predicts or determines that the first stage cannot provide adequate sensible cooling for the inside space.

12. (Currently Amended) In an HVAC system having a heating unit sized to heat an inside space under an expected heating load and a cooling unit sized to cool the inside space under an expected cooling load, the improvement comprising:

a controller adapted to determine whether the space is above a predetermined humidity threshold; and if so, operating both the heating unit and the cooling unit in unmodulated states that are not dependent on an output temperature of air provided to the inside space.

13. (Original) An HVAC system according to claim 12, wherein the controller is further adapted to determine if the temperature of the inside space is above a predetermined temperature, and if so, activating the cooling unit and not the heating unit, regardless of the humidity in the inside space.

14. (Original) An HVAC system according to claim 12, wherein the controller is adapted to operate both the heating unit and the cooling unit only if the temperature in the inside space is below a predetermined cooling set point.

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

15. (Original) An HVAC system according to claim 14, wherein the controller is adapted to operate the cooling unit and not the heating unit if the temperature in the inside space is above a predetermined cooling set point.

16. (Currently Amended) A method of updating an HVAC system having a heating unit sized to heat an inside space under an expected heating load, a cooling unit sized to cool the inside space under an expected cooling load, and a controller, wherein the heating unit is a forced air furnace, the method comprising:

updating the controller to determining whether the humidity in the inside space is above a predetermined humidity level; and if so, operating both the heating unit and the cooling unit together.

17. (Original) A method according to claim 16, wherein the updating step further updates the controller to determine whether the temperature of the inside space is above a predetermined temperature, and if so, only activating the cooling unit and not the heating unit, regardless of the humidity in the inside space.

18. (Original) A method according to claim 16, wherein the updating step further updates the controller to operate both the heating unit and the cooling unit only if the temperature in the inside space is below a predetermined cooling set point.

19. (Currently Amended) A computer-readable medium having stored thereon a computer program for controlling an HVAC system that services an inside space which, when executed by a controller, is capable of performing the following steps:

determining whether the humidity in the space is above a predetermined humidity level, and if so, activating both a heating unit and a cooling unit of the HVAC system; wherein the heating unit is activated to provide an unmodulated heat output.

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

20. (Previously Presented) A computer-readable medium according to claim 19, wherein the computer program when executed by the controller, is also capable of performing the follow step:

determine if the temperature of the inside space is above a predetermined temperature, and if so, activating only the cooling unit and not the heating unit.

21. (Currently Amended) A method of controlling an HVAC system having a heating unit sized to heat an inside space under an expected heating load and a cooling unit sized to cool the inside space under an expected cooling load, the heating unit and cooling unit configured to selectively operate in an ~~relatively constant~~ "on" state or an "off" state, the method comprising:

determining whether the humidity in an inside space is above a predetermined humidity threshold, and if so, operating both the heating unit and the cooling unit in their ~~relatively constant~~ "on" states; wherein the heating unit provides an un-modulated thermal output in the relatively constant "on" state.

22. (Currently Amended) A method of controlling an HVAC system having a heating unit sized to heat an inside space under an expected heating load and a cooling unit sized to cool the inside space under an expected cooling load, the method comprising:

determining whether the humidity in an inside space is above a predetermined humidity threshold, and if so, operating both the heating unit of the HVAC system and the cooling unit of the HVAC system, wherein the thermal output of the heating unit of the HVAC system is not dependent on a temperature of an air stream exiting the HVAC system.

23. (Currently Amended) A method of controlling an HVAC system having a heating unit and a cooling unit, the method comprising:

operating the cooling unit to satisfy a call for cooling for the inside space; and
after the call for cooling has been satisfied, determining if the latent cooling demands

Appl. No. 10/632,788
Response Dated December 8, 2004
Reply to Office action dated October 6, 2004

have been met, and if not, operating both the heating unit and the cooling unit; wherein the heating unit provides an unmodulated thermal output.

24. (New) The method of claim 1, wherein the heating unit is a forced air furnace.

25. (New) The method of claim 1, wherein the thermal output of the heating unit and the thermal output of the cooling unit are not balanced when they are operated in their "on" states.

26. (New) The method of claim 1, wherein an ambient temperature of the inside space is appreciably effected when both the heating unit and cooling unit are operated in their "on" states.

27. (New) A method of controlling an HVAC system having a heating unit, a cooling unit, and a controller, the heating unit and the cooling unit configured to selectively operate in a "on" state or an "off" state, the method comprising:

determining whether the humidity in an inside space is above a predetermined humidity threshold, and if so, operating both the heating unit and the cooling unit in their "on" states, wherein the thermal output of the heating unit is not modulated by the controller when the heating unit is in its "on" state.